Input Voltage with 78M08: 10V-25V

Input Voltage without 78M08: 5-12V*

Power: 25-88 mA

Range up to 100m

BTM-222 Class 1 Bluetooth


4800bps-460.8Kbps baud rate

Bluetooth Serial Adaptor

Slave/Master mode

L/W/H: 53mm X 35mm X 5mm

Place for SMD antenna



COPYRIGHT 2010 BEXPRO

Pins:

1. V-Input


2. GND

3. Bluetooth Link - LED positive Voltage (+) - for 10-14 V Input Voltage 220R Resistor on board

4. TX -> RX RS232 PC or Hardware RS-232 Transmitter Outputs

5. RX <- TX RS232 PC or Hardware RS-232 Receiver Inputs

6. ----no pin----




Changing Input Voltage:

desolder 78M08 - gray

connect 2 pads - red

now only LM11173.3MP will work - Input Voltage is 5-12 V



COPYRIGHT 2010 BEXPRO

Power-Supply Current:

max Current 100mA

min Current 15mA

Slave BT VISIBLE	Slave BT NOT VISIBLE	Master VISIBLE/HIDE
60mA	25mA	88mA

Read also specifications of BTM-222, LM1117MP3.3 and 78M08CDT

COPYRIGHT 2010 BEXPRO